




- Degree of protection: IP66
- Ambient temperature: -25–35 °C
- Impact strength: IK10
- Life time: 50000 hours
- System efficacy: 160 lm/W
- Colour rendering index CRI: 80-89, 4000–4000 K
- Chromaticity tolerance (initial MacAdam): SDCM3
- Cable glands: PG 13.5 thread
- Protection class: I
- Max. number of luminaires per circuit breaker B16: 36
- Max. number of luminaires per circuit breaker C16: 61
- Flickering value Pst LM: 1
- Power factor: 0,97
- Stroboscope effect value SVM: 0,4
- Total harmonic distortion: 6
- Energy efficiency class of the light source: D

- Body: grey PC (high mechanical resistance, UV stability, RAL 7035)
- Diffuser: translucent PC (high mechanical resistance, UV stability)
- Reflector: steel sheet, white (RAL 9003)
- Clips: stainless steel + polyamide
- Sealing: polyurethane (PUR), foam-filled base groove
- Connection: screwless five-pole terminal block, 5-wire connecting cabling for feed-through installation (1.5 mm2 cross-section, 2.5 mm2 available on demand)
- Unique design, resistant against humidity and dust, with IP66 enclosure rating and built-in aluminium heat sinks
- Type BVPB-01 polyamide vent plug, size M12x1.5
- Optimal mounting height: 3.5 to 10 m
- ON/OFF electronic driver (AC, DC on demand)



Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
76442	FUTURA 2.5ft VP PCc AI 16000/840 3F	35	17440	16390	102,2	160	3,9	1452	940

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %


FEATURES



CERTIFICATION



DOWNLOAD





76442

FUTURA 2.5ft VP PCc AI 16000/840 3F

8590515764426

